

GLASS PRODUCTS

Glass Technical Document

Use of Applied Films, Paints, Etc.

Please be advised that applied films, paints and/or any item that alters an insulated glass product should be avoided. Applied films, paints, etc. are typically applied to the number one, number four or number six surface of an insulated/insulated laminated unit and alter the solar performance and/or thermal properties of the glass product. Typically, applied film or paint is limited to the daylight opening size of the framing system, which increases the temperature differential between the edge of the glass, contained in the glazing pocket, and the center of the glass. The differential is further accentuated if a solar control glass product, which uses a low-e coating, has been incorporated into the IGU configuration. Any increased differential in temperature can result in glass failure.

Further, no testing has approved any film and/or paint in conjunction with glass. There are a plethora of available types of films sourced from various manufactures with no consistency relative to the adhesives. Paints tend to off-gas at high temperatures, resulting in residue deposits that are visually apparent and objectionable over time. It is for these, and many other reasons, that applied films and/or paints should be avoided. For your information, the application of an applied film and/or paint voids most insulated glass manufacturer's warranties.

In summary, Tristar Glass will not provide a warranty for insulated glass units that incorporate the use of applied films and/or paints.

Sincerely,
TriStar Glass Products
Gregory A. Oehlers
Executive Director Architectural Sales

TULSA 1120 MAIN PARKWAY CATOOSA, OK 74015 DALLAS 1790 WESTPARK DRIVE GRAND PRAIRIE, TX 75050 HOUSTON 19522 ALDINE WESTFIELD HOUSTON, TX 77073